

Colourman Paints Shellac Primer

PRODUCT DATA

Description:

The ultimate shellac-based primer and stain blocker. Offering excellent adhesion to glossy surfaces - even glass. Blocks stubborn and persistent stains. The advanced shellac formula seals porous surfaces with excellent enamel holdout, even sealing bleeding knots and sap streaks. Suitable for use on water stains, fungal degradation, nicotine, oil stains, marker pen stains and more. Designed to permanently block odours (from smoke and fire damage to odours from pets and nicotine). The dried film is non-toxic and hypo-allergenic and may be used in areas where incidental contact with food items occur. Ideal for interior ceilings, walls, doors and general paintable surfaces. Including spot priming on wood, metal, trims and PVC.

Area of use:

Interior

Substrates:

Plaster, wood, previously painted surfaces

Packing:

1 Litres & 2.5 Litres

Physical Constants:

Colour:	White
Finish:	Matt
Volume solids:	25%
Theoretical spreading rate:	Approx. 12-15 sq. metres per litre
Specific gravity:	1.34
Flash point:	17°C
Dry to touch:	20 mins
Over-coating time:	1 hour

**The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

Application Details:

Application method:	Brush / Roller / Spray
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface Condition: The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease and oil.

Please refer to the Material Safety Data Sheet for further information.