



COLOURMAN[®]
PAINTS
Est. 1984

Colourman Paints Shellac Sanding Sealer

PRODUCT DATA

Description

A shellac sanding sealer made from a blend of shellacs and zinc stearate, which is ideal for sealing new or stripped wood prior to waxing and French polishing. Ease of sanding ensures a perfect finish.

Area of use

Interior

Substrates

Wood

Packing

500ml, 2.5 litres and 5 litres

Physical Constants

Colour:	Transparent
Finish:	Gloss
Volume solids:	25%
Theoretical spreading rate:	18 sq. metres per litre
Flash point:	18°C
Specific gravity:	0.87
Dry to touch:	5 - 10 minutes (20°C)
Over-coating time:	15 minutes

***The theoretical spreading rate** has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. **The physical constants** are subject to normal manufacturing tolerances.

Application Details

Application method:	Cloth or Pad
Thinner:	Methylated Spirit
Cleaning of tools:	Methylated Spirit

Surface condition The surface should be stable, firm, dry and free of dust, sand, dirt, grease and oil.

Please refer to the Material Safety Data Sheet for further information.
For additional guidance please contact your local Technical Sales Representative.